

## FISA TEHNICA DEBITMETRU AXIAL

Debitmetru apa rece, axial, tip WDE-K50, Woltman, cu cadran uscat, cu 6 role, omologat MID R100-HV, cu flanse, pregatit pentru echiparea ulterioara cu module inductive fabricat din materiale de cea mai buna calitate, rezistente la coroziune.



Dimensiune	mm (in)	50 (2")	65 (2"1/2)	80 (3")	100 (4")	125 (5")	150 (6")	200 (8")	
Suprasarcina Q <sub>4</sub>	m <sup>3</sup> /h	50	78,75	125	200	200	312,5	500	
Debit permanent Q <sub>3</sub>	m <sup>3</sup> /h	40	63	100	160	160	250	400	
Debit minim Q <sub>1</sub>	m <sup>3</sup> /h	0,40	0,63	1,00	1,60	1,60	2,50	4,00	
Presiune maxim admisibila	bar	16							
Domeniu de indicare maxim	m <sup>3</sup>	999.999					9.999.999		

Dimensiune	mm (in)	50 (2")	65 (2"1/2)	80 (3")	100 (4")	125 (5")	150 (6")	200 (8")
L	mm	200	200	225	250	250	300	350
H	mm	130	130	152	152	152	181	181
h	mm	78	86	95	104	117	133	162
Greutate	kg	8,5	9,5	13,50	15	20,5	30,50	43

